

WHAT IS CLAIMED IS:

Sub 1

1. A method for testing a solar panel including, at least, both a solar cell and an outer housing, the method comprising:

performing one of a withstand voltage test and an insulation resistance test between a live electrical section electrically connected to the solar cell and a conductor section of the outer housing, and thereafter

applying a voltage between the live electrical section and the conductor section.

2. The method according to claim 1, wherein the voltage applied between the live electrical section and the conductor section is an alternating current voltage.

3. The method according to claim 1, wherein the outer housing is a bottom surface reinforcement member for reinforcing the bottom surface of the solar panel.

4. The method according to claim 1, wherein the solar panel comprises a metal plate.

5. The method according to claim 4, wherein the metal plate is a stainless steel sheet.

6. The method according to claim 1, wherein the voltage applied between the live electrical section and the conductor section of the outer housing is fed from a utility power line.

7. A method for inspecting a solar panel generating system including a solar panel including, at least, both a solar cell and an outer housing, the method comprising:

performing one of a withstand voltage test and an insulation resistance test between a live electrical section electrically connected to the solar cell and a conductor section of the outer housing, and thereafter

applying a voltage between the live electrical section and the conductor section.

8. An apparatus for testing a solar panel including, at least, both a solar cell and an outer housing, the apparatus comprising:

a means for performing one of a withstand voltage test and an insulation resistance test between a live electrical section electrically connected to the solar cell and a conductor section of the outer housing, and

a means for applying a voltage between the live electrical section and the conductor section after the one

Cond

of the withstand voltage test and the insulation resistance test has been performed.

9. The apparatus according to claim 8, wherein the voltage applied between the live electrical section and the conductor section is an alternating current voltage.

10. The apparatus according to claim 8, wherein the outer housing is a bottom surface reinforcement member for reinforcing the bottom surface of the solar panel.

11. The apparatus according to claim 8, wherein the solar panel comprises a metal plate.

12. The apparatus according to claim 11, wherein the metal plate is a stainless steel sheet.

13. The apparatus according to claim 8, wherein the voltage applied between the live electrical section and the conductor section of the outer housing is fed from a utility power line.

14. An apparatus for inspecting a solar panel generating system including a solar panel including, at least, both a solar cell and an outer housing, the apparatus

Cont

comprising:

a means for performing one of a withstand voltage test and an insulation resistance test between a live electrical section electrically connected to the solar cell and a conductor section of the outer housing, and

a means for applying a voltage between the live electrical section and the conductor section after the one of the withstand voltage test and the insulation resistance test has been performed.

15. A method for manufacturing a solar panel including, at least, a solar cell, a surface protective covering member for encapsulating the solar cell, and an outer housing, the method comprising:

encapsulating the solar cell with the surface protective covering member;

performing one of a withstand voltage test and an insulation resistance test between a live electrical section electrically connected to the solar cell and a conductor section of the outer housing; and thereafter

applying a voltage between the live electrical section and the conductor section.

16. An insulation resistance measuring apparatus comprising a means of applying a voltage across test

CONFIDENTIAL

terminals subsequent to an insulation test.

17. A withstand voltage tester comprising a means of applying a voltage across test terminals subsequent to a withstand voltage test.

A1  
const

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100